

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 974 811 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
03.11.2004 Bulletin 2004/45

(51) Int Cl.7: **G01B 11/24**

(21) Application number: **99304721.6**

(22) Date of filing: **16.06.1999**

(54) **Digital cameras**

Digitalkameras

Caméras numériques

(84) Designated Contracting States:
DE FR GB

(30) Priority: **21.07.1998 US 120096**

(43) Date of publication of application:
26.01.2000 Bulletin 2000/04

(73) Proprietor: **Hewlett-Packard Company,
A Delaware Corporation
Palo Alto, CA 94304 (US)**

(72) Inventor: **Allen, Ross R.
Belmont, California 94303 (US)**

(74) Representative: **Powell, Stephen David et al
WILLIAMS POWELL
Morley House
26-30 Holborn Viaduct
London EC1A 2BP (GB)**

(56) References cited:
**US-A- 4 111 557 US-A- 4 914 460
US-A- 5 753 931**

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 0 974 811 B1

Description

[0001] The present invention relates generally to digital cameras, and more particularly, to a digital camera capturing technique for documents.

[0002] Projecting one or more points onto an object and detecting the projected points using an autofocus detector is the basis of so-called active (but nonacoustic) autofocus mechanisms in typical point-and-shoot cameras. Cameras can reliably determine the focal distance to a small area on an object, but cannot determine if an object is imaged obliquely, as can be the case with handheld exposures of documents. Cameras can indicate to the user that an object is too close to focus upon, but do not indicate that the depth of focus is inadequate to image an entire object. Determining the adequacy of the depth of focus of an entire object represents a complex problem that is typically left to the user. However, manual procedures, such as stopped-down viewfinder techniques used by skilled photographers, are very inconvenient and prone to error particularly in low-contrast situations in a stopped-down viewfinder.

[0003] US-A-4, 111,557 discloses an arrangement for detecting departures of shape from an ideal shape of an object which is illuminated with a light pattern from a projection, the light pattern being scanned by a separate receiving unit connected to a computing unit.

[0004] According to a first aspect of the present invention, there is provided a handheld digital camera comprising emitter circuitry arranged to project a pattern on an object, and, fixed relative to the emitter circuitry, image sensor circuitry for detecting an orientation of the object relative to an optical axis of the digital camera by detecting the projected pattern and then capturing the object.

[0005] Multiple beams of light may be emitted, and the beams are preferably parallel.

[0006] The multiple beams of light may comprise infrared beams or diverging beams of light.

[0007] The camera may store in a memory data that represents the orientation of the object and the planarity of the object.

[0008] An image processor may determine a planarity of the object and the apparatus may further comprise a plurality of emitters, the plurality of emitters projecting the spot pattern on the object. The image sensor may comprise a plurality of CMOS sensors and/or logic means that processes the projected spot pattern to determine the planarity and/or the orientation of the object, wherein the object comprises a document.

[0009] The image sensor may detect multiple beams of light projected on the object, wherein the object comprises a document, whereby the image processor analyses a detection of the multiple beams of light projected on the document to determine an orientation of the document, the planarity of the document, a curl of the document, and a distance of the document.

[0010] According to a second aspect of the present

invention, there is provided a method for a handheld digital camera capturing technique for documents, the method comprising: projecting a spot pattern on a document to be captured by the digital camera; detecting the projected spot pattern; analysing the projected spot pattern to determine an orientation of the document relative to an optical axis of the digital camera and a planarity of the document.

[0011] Data representing the orientation and planarity of a document may be processed prior to capturing the document, whereby the image sensor captures the document in sharp focus and without geometric distortions. Multiple exposures of the document may be processed to capture portions of the document that are at multiple distances in sharp focus. The method may further comprise outputting a signal to indicate that the digital camera should be reoriented with respect to the document.

[0012] The projected spot pattern may be analysed to determine a distance of the document from the digital camera.

[0013] In one embodiment, the present invention is incorporated into a digital camera to permit compensation to be performed for the following effects in the handheld capture of documents at close range:

- the optical axis of the camera is not aligned with a normal to the surface of the document;
- the depth-of-field for optics used for capture within 0.5 - 1 meter from the focal plane of the image sensor is limited, so proper focus is critical; and
- typical documents may not be planar, for example, pages bound in a book.

This embodiment extends the concept of auto-focus for cameras to auto-focus and auto-orientation, and provides an indication of the orientation of the optical axis with respect to the normal to the plane of the document and an indication of the degree of planarity of the document (e.g., including page curl of the document).

[0014] A typical active autofocus camera employs an infrared emitter and a photodetector arranged on either side of the optical axis. As the shutter release is pressed part-way, a highly-collimated IR beam is projected (usually as a vertical bar) on the subject, and the position of the beam is imaged on the detector. The measurement of range relies on parallax between the emitter and detector.

[0015] In one embodiment, the present invention involves projecting beams of visible or, preferably, infrared (IR) light on the document to be captured in a predetermined pattern (e.g., a spot pattern) as the shutter release is pressed part-way. The projected pattern is designed to provide information of range, orientation, and planarity of the document. The pattern is received by the image sensor in the digital camera and stored (or processed) immediately before the capture of the subject image using the image sensor. Using IR illumination provides an invisible measurement and uses the sensitivity

of, for example, commercially available CCD and CMOS sensors to IR wavelengths. High intensity IR-LEDs are commercially available for use as emitters.

[0016] A pattern to provide range and alignment can be provided by projecting three beams of light in a pattern. More robust patterns for measuring planarity of the subject can employ more than three beams of light, for example, to provide a grid of multiple cells.

[0017] In one embodiment, a method for a digital camera capturing technique includes determining an orientation of an object (e.g., a document) relative to an optical axis of the digital camera, and determining a distance of the object from the digital camera. The method also includes determining a planarity of the object. The method further includes projecting a pattern on the object, and detecting the projected pattern, which is then processed to determine the orientation of the object relative to the optical axis of the digital camera, the distance of the object from the digital camera, and the planarity of the object.

[0018] Other aspects and advantages of the present invention will become apparent from the following detailed description and accompanying drawings.

FIG. 1a shows a regular 5-by-5 array of spots of light (a spot pattern) projected on an object, and FIGs. 1b-1e show examples of the spot pattern for various object orientations and positions in accordance with one embodiment of the present invention.

FIGs. 2a-2e are similar to FIGs. 1a-1e but with a spot pattern that includes only four spots in accordance with another embodiment of the present invention.

FIGs. 3a and 3b present an imaging approach for detecting distance and orientation of the object to be captured in accordance with one embodiment of the present invention.

FIG. 4 presents an imaging approach for detecting distance and orientation of the object to be captured in accordance with another embodiment of the present invention.

FIG. 5 shows a digital camera in accordance with one embodiment of the present invention.

FIG. 6 is a flow diagram of the operation of the digital camera of FIG. 5 in accordance with one embodiment of the present invention.

FIG. 7 is a block diagram of the digital camera of FIG. 5 shown in greater detail in accordance with one embodiment of the present invention.

[0019] There are many usability issues and technical limitations in handheld document imaging. Some of the current generation of digital cameras have a document capture mode, but the low pixel count in the image sensors of the current generation of digital cameras makes them useful only for small documents, such as business cards. However, in the future, affordable digital cameras will likely have more than four million pixels, which will

allow for full-page documents to be captured at a high level of document quality.

[0020] Accordingly, the present invention provides a digital camera capturing technique for documents. In one embodiment, the present invention uses projected beams of light (e.g., a spot pattern) and an image sensor of a digital camera to determine a distance, an orientation, and a planarity of an object to be captured. It is assumed that the spots are sharply imaged on the image sensor, which generally requires that the camera's autofocus system provide a useful, approximate focal distance measurement so that camera optics can be adjusted for optimal focus at close range. An object detected at close range automatically activates the document capture mode with its beam emissions and processing described herein. Measurement of the intensity distribution for each imaged spot provides an indication of the sharpness of focus and the usefulness of the spot for measurement purposes.

FIG. 1a shows a regular 5-by-5 array of spots of light projected on an object in accordance with one embodiment of the present invention. It is not necessary to have a regular array so long as the arrangement of the spots is taken into account when processing the acquired image of the spots on the object to be captured. FIGs. 1b-1e show examples of the spot pattern of FIG. 1a for various object orientations and positions in accordance with one embodiment of the present invention.

FIG. 1b shows an example image of the spot pattern when the object is pitched and rolled with respect to the optical axis.

FIG. 1c shows an example image of the spot pattern when the object is pitched with respect to the optical axis.

FIG. 1d shows an example image of the spot pattern where the optical and normal axes are coincident near the right-half of the object, but it is a book which is nonplanar, and the spots on the left indicate curvature of the object out of the plane, which is often referred to as page curl.

FIG. 1e is another example of the image of the spot pattern projected onto an open, bound book where there is pitch of the surface as well as curvature.

FIGs. 2a-2e are similar to FIGs. 1a-1e but with a spot pattern that includes only four spots in accordance with another embodiment of the present invention.

FIGs. 3a and 3b present an imaging approach for detecting distance and orientation of the object to be captured in accordance with one embodiment of the present invention. We assume the following for the sake of illustration of the general principle:

- The object is a predominantly planar surface whose normal vector has an arbitrary angular rotation with respect to the camera's optical axis.

is.

- The rotation of the plane is about a vector perpendicular to the plane of emitters 1A and 2A in FIGS. 3a and 3b.
- Beams 1 and 2 are parallel to the optical axis and thereby form a plane containing all the points indicated in FIGs. 3a and 3b. This parallelism is not a requirement for this technique to work (e.g., FIG. 4 illustrates the use of diverging beams).

[0021] In a general case, the rotation of the plane is about an axis that is not perpendicular to the plane formed by beams 1 and 2. Some curvature of the object surface is allowed, for example, pages in a bound book and documents printed upon or wrapped around a cylinder.

[0022] In FIG. 3a, emitters 1A and 2A project beams 1 and 2 parallel to the optical axis. Object orientation A shows a plane rotated with respect to the optical axis (e.g., an oblique parallel projection). Beams 1 and 2 produce spots 1B and 2B, respectively. The images of spots 1B and 2B projected by the camera's lens onto its image sensor are 1C and 2C, respectively.

[0023] The orientation and distance of the plane can be determined from the distances $I-1C$ (the distance between two points A and B is denoted as $A-B$) and $I-2C$. These distances can be measured in pixels on the image sensor in the camera's image plane. The inequality of $I-1C$ and $I-2C$ indicates that the plane is pitched with respect to the optical axis.

[0024] When the plane is rotated to align its normal with the optical axis, beams 1 and 2 produce spots 1B and 2D, respectively, for example, in object orientation B, which are imaged as points 1C and 2E, respectively. In this case, $I-1C$ and $I-2E$ are identical, indicating alignment of the normal vector and the optical axis.

[0025] FIG. 3b demonstrates distance measurement when the plane is perpendicular to the optical axis and translated between two positions (e.g., an orthographic parallel projection). In position A, beams 1 and 2 produce spots 1B and 2B on the object that are imaged as 1C and 2C, respectively. The distance to the object can be computed from $I-1C$ and $I-2C$. Moving the object farther away, beams 1 and 2 produce spots 1D and 2D that are imaged as 1E and 2E, respectively. Because the distance $I-1C$ is greater than $I-1E$, the object in position B is determined to be further away than the object in position A.

[0026] In this example, there is a single rotation of the object's normal with respect to the imaging axis, and beams 1 and 2 are parallel to the optical axis. The calculation of distance and orientation of the object represents an application of planar trigonometry using known, fixed distances in the projection and imaging system and the position of the imaged spots.

[0027] The distance between points 1A and 1B, $1A-1B$, is computed as follows. It is assumed, in this exam-

ple, that emitters 1A and 1B are located in the image plane (which introduces a constant in the calculation that can be omitted for clarity). By similar triangles, we know that

$$\frac{1A-1B}{I-F} = \frac{1A-1C}{I-1C}. \quad (1)$$

Solving for the only unknown,

$$1A-1B = \frac{1A-1C}{I-F} * (I-F/I-1C) \quad (2a)$$

and using the relation between fixed distances $1A-1C = I-1A + I-1C$,

$$1A-1B = I-F * (I-1A/I-1C). \quad (2b)$$

Similarly, it can be shown that

$$2A-2B = I-F * (I-2A/I-2C) \quad (3)$$

[0028] An optimal focal distance for document capture can be computed from $1A-1B$ and $2A-2B$ taking into account the depth of field for the lens at its working aperture.

[0029] The situation of a rotated object places demands on the camera's ability to deliver sharp focus across the document: for example, portions of the document may lie outside the camera's depth-of-focus. In this case, information obtained by the present invention can be used to make multiple exposures, each at different working distances, in order to capture the document piece-wise in sharp focus. Alternatively, the information that the camera's depth-of-focus is exceeded could be used to generate a signal to inform the user to reorient the camera with respect to the document. This information, which typically cannot be determined from a single autofocus measurement at a point on a document, provides a valuable feature for opportunistic and casual capture of documents where precise alignment between the camera and the object cannot be or is not obtained.

[0030] The angle θ that the plane makes with the optical axis in object orientation A in FIG. 3a is

$$\arcsin((2A-2B - 1A-1B) / 1A-2A). \quad (4)$$

[0031] The constructions in FIGs. 3a and 3b and equations (1) - (4) show that, for parallel beams, it is desirable to maximize the offsets of the emitters from the optical axis (i.e., $I-1A$, $I-2A$) to achieve the maximum pixel count for $I-1C$ and $I-2C$. Achieving the maximum pixel count for $I-1C$ and $I-2C$ provides the greatest resolution in equations (2b), (3), and (4) given the discrete

number of pixels.

[0032] In the general case, where the rotation of the object is along a vector that is not perpendicular to the plane of emitters 1 and 2, more complex geometric transforms than equations (1) - (4) are required and would be apparent to one of ordinary skill in the art.

[0033] Planarity (e.g., distortion) of an object to be captured is determined, for example, using a spot pattern that includes more than 4 spots and by applying the above discussed logic to such a spot pattern. "Digital Image Warping", George Wolberg, IEEE Computer Society 1990, pp. 52-56, discusses the principle of a 4-dot matrix for perspective transformations, and is incorporated herein by reference in its entirety.

[0034] FIG. 4 shows another embodiment in which emitters 3A and 4A are placed together on the optical axis and project a pattern using non-parallel (diverging) beams aimed toward the object. The non-parallel beams produce spots 3B and 4B on a rotated object. The images of these points at the camera's focal plane sensor are 3C and 4C, respectively.

[0035] In particular, FIG. 4 illustrates the different results for parallel beams 1 and 2 and divergent beams 3 and 4. It is observed that the difference $I-3C - I-4C$ is small for two significantly different distances $3A-3B$ and $4A-4B$. This observation suggests that the co-located, diverging beam method has less sensitivity and greater susceptibility to discretization errors than the parallel beam method, where the difference $I-1C - I-2C$ generally provides greater sensitivity.

[0036] FIG. 5 shows a digital camera 50 in accordance with one embodiment of the present invention. Digital camera 50 includes IR emitters 1A, 1A', 2A, and 2A' arranged around the optical axis of the camera's imaging system at a displacement that represents a reasonable compromise between usability and sensitivity. Digital camera 50 also includes an active autofocus emitter 51, a viewfinder 52, an autofocus detector 53, an orientation/range emitter 54, and an imaging lens 55.

[0037] FIG. 6 is a flow diagram of the operation of the digital camera of FIG. 5 in accordance with one embodiment of the present invention. As the shutter release of digital camera 50 is pressed, digital camera 50 projects a spot pattern using IR emitters 1A, 1A', 2A, and 2A' to emit parallel IR beams on the object at stage 61. Digital camera 50 detects the spot pattern on its image sensor (see FIG. 7) at stage 62. Digital camera 50 determines the orientation of the object at stage 63, as discussed above with respect to FIGs. 3a and 3b. Digital camera 50 determines the planarity of the object at stage 64, as discussed above with respect to FIGs. 3a and 3b. Digital camera 50 can also determine the distance of the object from digital camera 50, as discussed above. Further, digital camera 50 can determine a (page) curl of the object, for example, in which the object is a document such as a page in a bound book.

[0038] Digital camera 50 then processes this information accordingly, as discussed above with respect to

FIGs. 3A and 3B. Alternatively, digital camera 50 can emit non-parallel beams of light and perform stages 63 and 64 as discussed above with respect to FIG. 4. For example, output from orientation, planarity, and page curl determinations can be used by image processing algorithms to render a planar, undistorted image of a document captured obliquely and with page curl (e.g., a page of a bound book).

[0039] FIG. 7 is a block diagram of the digital camera of FIG. 5 shown in greater detail in accordance with one embodiment of the present invention. In FIG. 7, digital camera 50 includes an ASIC 72 (Application Specific Integrated Circuit) that is in communication with orientation/range emitters 1A, 1A', 2A, and 2A', active autofocus emitter 51, viewfinder 52, autofocus detector 53, a memory 76 (e.g., a conventional random access memory that is used to store a captured digital image of a document) via a bus 74, and an image sensor 78 (e.g., a photodetector array that includes CMOS sensors for detecting IR light emitted from emitters 1A, 1A', 2A, and 2A'). For example, image sensor 78, which is used for image capture, is first used to acquire information relating to the distance, orientation, planarity, and curl of the document to be captured using the projected spot pattern (e.g., obtaining real-time information from a pre-exposure).

[0040] ASIC 74 represents a main ASIC of the digital camera. ASIC 74 performs image processing. For example, the image processing involved in the present invention can be implemented on image processing ASIC 74. For example, the logic for performing the digital camera capturing technique can be implemented in a hardware description language, such as the Verilog™ hardware description language, described, for example, in D.E. Thomas, J.P. Moorby, "The Verilog™. Hardware Description Language" (1991). Thus, the logic for performing the digital camera capturing technique can be implemented in the Verilog™ hardware description language, and the corresponding circuitry can be implemented using methods known in the art to provide an image processing ASIC for performing the digital camera capturing technique in accordance with one embodiment of the present invention (e.g., an ASIC implementation including logic that performs 3D geometrical transformations using a lookup table for inverse trigonometric calculations).

[0041] In one embodiment, the present invention includes the following:

- providing physical measurements describing the distance, shape (e.g., planarity, such as curl of a document), orientation of an object (e.g., a document), and curl of the object to be captured with respect to the optical axis of a camera;
- providing measurements of the distance, shape, orientation, and curl of a document to an image processor such that the document can be rendered as a planar object without geometric distortions;

- provides an indication of the angular-orientation of a camera's optical axis with respect to a normal to the surface of an object;
- provides an indication of the planarity of an object;
- operates in conjunction with the camera's active or passive range-finding system to detect a close-focus situation and enhance the capture of documents at close focal distances;
- provides a signal to the camera's exposure architecture that multiple exposures at different focal distances are required to render the document given limitations on the camera's depth of focus in close-focus situations; and
- provides an indication to the user that the camera must be reoriented with respect to the document to properly capture the document.

[0042] Although particular embodiments of the present invention have been shown and described, it will be obvious to those skilled in the art that changes and modifications can be made without departing from the present invention in its broader aspects. For example, the present invention can be implemented in hardware or software or a combination of hardware and software. The present invention can also be implemented using any number and arrangement of orientation/range emitters providing a variety of spot patterns for image processing. The image sensor circuit can be implemented using CMOS sensors, CCD sensors, or other types of sensors that can detect a projected spot pattern. Therefore, the appended claims are to encompass within their scope all such changes and modifications that fall within the true scope of the present invention.

Claims

1. A handheld digital camera (50) comprising emitter circuitry (1A, 1A', 2A, 2A') arranged to project a pattern (1B, 2B) on an object, and, fixed relative to the emitter circuitry, image sensor circuitry (78) for detecting an orientation of the object relative to an optical axis of the digital camera by detecting the projected pattern and then capturing the object.
2. The camera of claim 1 wherein the image sensor circuitry is arranged to detect a planarity of the object.
3. The camera of claim 1 wherein the image sensor circuitry is arranged to detect a curl of a document.
4. The camera of claim 3 further comprising image processing circuitry (74) is arranged to process a detection of the projected pattern to determine the orientation of the document and the planarity of the document.

5. The camera of any preceding claim, wherein the emitter circuitry (1A, 1A', 2A, 2A') produces a projected pattern (1B, 2B) of at least four projected spots.
6. The camera of any of claims 1 to 4, wherein the emitter circuitry (1A, 1A', 2A, 2A') produces a projected pattern comprising multiple beams of light.
7. The camera of any preceding claim wherein the emitter circuitry includes a plurality of emitters (1A, 1A', 2A, 2A') and the image sensor circuitry (78) responds to beams passing through a lens (55) of the camera, and wherein the emitters are located around the edge of the lens.
8. A method for a handheld digital camera (50) capturing technique for documents, the method comprising:

projecting a spot pattern (1B, 2B) on a document to be captured by the digital camera;
detecting the projected spot pattern;
analysing the projected spot pattern to determine an orientation of the document relative to an optical axis of the digital camera and a planarity of the document.

Patentansprüche

1. Eine tragbare Digitalkamera (50), die einen Emitterschaltungsaufbau (1A, 1A', 2A, 2A'), der angeordnet ist, um ein Muster (1B, 2B) auf ein Objekt zu projizieren, und einen relativ zu dem Emitterschaltungsaufbau festen Bildsensorschaltungsaufbau (78) zum Erfassen einer Ausrichtung des Objekts relativ zu einer optischen Achse der Digitalkamera durch ein Erfassen des projizierten Musters und ein darauffolgendes Erfassen des Objekts aufweist.
2. Die Kamera gemäß Anspruch 1, bei der der Bildsensorschaltungsaufbau angeordnet ist, um eine Planarität des Objekts zu erfassen.
3. Die Kamera gemäß Anspruch 1, bei der der Bildsensorschaltungsaufbau angeordnet ist, um ein Zusammenrollen eines Dokuments zu erfassen.
4. Die Kamera gemäß Anspruch 3, die ferner einen Bildverarbeitungsschaltungsaufbau (74) aufweist, der angeordnet ist, um eine Erfassung des projizierten Musters zu verarbeiten, um die Ausrichtung des Dokuments und die Planarität des Dokuments zu bestimmen.
5. Die Kamera gemäß einem der vorherigen Ansprüche, bei der der Emitterschaltungsaufbau (1A, 1A',

2A, 2A') ein projiziertes Muster (1B, 2B) von zumindest vier projizierten Punkten erzeugt.

6. Die Kamera gemäß einem der Ansprüche 1 bis 4, bei der der Emitterschaltungsaufbau (1A, 1A', 2A, 2A') ein projiziertes Muster erzeugt, das mehrere Lichtstrahlen aufweist.

7. Die Kamera gemäß einem der vorherigen Ansprüche, bei der der Emitterschaltungsaufbau eine Mehrzahl von Emittlern (1A, 1A', 2A, 2A') umfasst und der Bildsensorsschaltungsaufbau (78) auf Strahlen anspricht, die durch eine Linse (55) der Kamera laufen, und bei der die Emittler um den Rand der Linse positioniert sind.

8. Ein Verfahren für eine Dokumenten-Erfassungstechnik einer tragbaren Digitalkamera (50), wobei das Verfahren folgende Schritte aufweist:

Projizieren eines Punktmusters (1B, 2B) auf ein durch die Digitalkamera zu erfassendes Dokument;

Erfassen des projizierten Punktmusters;

Analysieren des projizierten Punktmusters, um eine Ausrichtung des Dokuments relativ zu einer optischen Achse der Digitalkamera und eine Planarität des Dokuments zu bestimmen.

Revendications

1. Appareil photo numérique de poche (50) comprenant un ensemble de circuits émetteurs (1A, 1A', 2A, 2A') agencés pour projeter une figure (1B, 2B) sur un objet et, fixé à l'ensemble de circuits émetteurs, un ensemble de circuits de détection d'image (78) pour détecter une orientation de l'objet par rapport à un axe optique de l'appareil photo numérique en détectant la figure projetée puis en capturant l'objet.
2. Appareil photo selon la revendication 1 dans lequel l'ensemble de circuits de détection d'image est agencé pour détecter une planarité de l'objet.
3. Appareil photo selon la revendication 1 dans lequel l'ensemble de circuits de détection d'image est agencé pour détecter une courbe d'un document.
4. Appareil photo selon la revendication 3 comprenant en outre un ensemble de circuits de traitement d'image (74) agencé pour traiter une détection de la figure projetée pour déterminer l'orientation du document et la planarité du document.

5. Appareil photo selon l'une quelconque des revendications précédentes, dans lequel l'ensemble de circuits émetteurs (1A, 1A', 2A, 2A') produit une figure projetée (1B, 2B) d'au moins quatre points projetés.

6. Appareil photo selon l'une quelconque des revendications 1 à 4, dans lequel l'ensemble de circuits émetteurs (1A, 1A', 2A, 2A') produit une figure projetée comprenant de multiples faisceaux de lumière.

7. Appareil photo selon l'une quelconque des revendications précédentes dans lequel l'ensemble de circuits émetteurs comprend une pluralité d'émetteurs (1A, 1A', 2A, 2A') et l'ensemble de circuits de détection d'image (78) réagit aux faisceaux traversant une lentille (55) de l'appareil photo, et dans lequel les émetteurs sont disposés autour du bord de la lentille.

8. Procédé pour une technique de capture de documents d'un appareil photo numérique de poche (50), le procédé comprenant :

la projection d'une figure de points (1B, 2B) sur un document à capturer par l'appareil photo numérique ;

la détection de la figure de points projetée ;

l'analyse de la figure de points projetée pour déterminer une orientation du document par rapport à un axe optique de l'appareil photo numérique et une planarité du document.




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 1D




FIG. 1E



FIG. 2A



FIG. 2B



FIG. 2C

FIG. 2D




FIG. 2E




FIG. 3A




FIG. 3B




FIG. 4




FIG. 5




FIG. 6




FIG. 7